

Model: Z8530



- Real-Time 4K Video Streaming
- 30x zoom using Sony's patented Super Resolution Zoom
- Stream 4K and HD resolutions
- Power over Ethernet (PoE)
- Supports Sony VISCA™ camera control over IP and ONVIF® Profile S

NEVER BEFORE HAS STREAMING 4K BEEN SO SIMPLE AND COST-EFFECTIVE

The Z3Cam-4K™ H.265 IP camera provides 4K Ultra-HD video streaming over Gigabit Ethernet networks. The Z3Cam-4K combines video compression expertise from Z3 Technology with Sony's proven 4K camera technology to provide the highest quality image at the lowest bandwidth, latency and power. This robust system brings clarity and detail to high movement and low light conditions featuring 30x zoom with integrated auto focus. Video with this clarity is a perfect fit for virtual reality imaging, high detail data analytics, broadcast, medical, surveillance and more! Upgrade to 4K and expand your reach with the Z3Cam-4K.

APPLICATIONS

Broadcast

Industrial

Medical

Security and Surveillance

Corporate



Details		
Camera Features	 30x optical zoom in 2160p30 mode using Sony's Super Resolution Zoom 40x optical zoom in 1080p30 mode using Sony's Super Resolution Zoom Noise reduction algorithm for high frequency and high detail areas Visibility enhancer ICR (Day and Night) High sensitivity image processor Easily mount to tripod or mounting bracket Leverages Sony's FCB-ER8530 4K camera module 	
Streaming Features	 H.265, H.264 or MJPEG encoded video over IP with no additional equipment and no distance limitations Supports 4K UHD and HD resolutions up to 30 fps (2160p, 1080p, 720p, and lower) Outputs RTP, RTSP, MPEG-2 TS or RTMP Simultaneously stream and/or record in multiple resolutions and bitrates Supports unicast and multicast streaming Compatible with Wowza Streaming Engine™ and YouTube Live* 	
Control	 Z3 web interface for Control and configuration Pass Sony VISCA™ Camera Control Commands over IP Supports ONVIF® Profile S Pelco-D PTZ control 	
Recording	Compressed USB recording	
Decoder Options	 Compatible with ZEUS® HE265-DEC decoder (also available from Z3 Technology) PC decoding 	

Specifications

73	m•4	Tm

- 1			
Interfaces	Gigabit Ethernet, USB 2.0, Audio Input and Composite Output		
Power	PoE or 12V DC		
Power Consumption	7.5W typical while encoding H.265/HEVC video		
Temperature & Humidity	Operating: -5 to 50 °C at 20-80% Relative Humidity	Storage:-10 to 60 °C at 20-80% Relative Humidity	
Mount	1/4 20 UNC tripod screw hole on bottom of unit		
Dimensions (L x W x H)	130 x 61 x 62 mm (5.1 x 2.4 x 2.4 in)		
Weight	682 g (1.5 lb)		
Package Contents	Z3Cam-4K camera and 12V Power Supply		
Additional Components	Add a wifi USB dongle for wireless connectivity**		

4K IP STREAMING

Z3CAM-4K™

H.265/HEVC 4K Encoding & IP Streaming







2160p30 H.265/HEVC PC Decoder

2160p30

Z3CAM-4K™

H.264 4K Encoding & IP Streaming







ZEUS® HE265-DEC 2160p30 H.265 Decoder





OPERATING CONTROLS



- 1 RS-232 Serial
- (2) USB 2.0
- 3 Audio Input
- (4) GigE with PoE Support
- (5) Status LED
- (6) Composite Output
- 7 12V DC Power

ORDERING OPTIONS

Z3Cam-4K™ Model: Z8530 Complete Solution

- 4K IP Camera
- Power Supply
- Serial Cable
- Documentation

**Contact Z³ Technology for Customized Product Options sales@Z3technology.com +1.402.323.0702 www.Z3technology.com



Z3 Technology®