



FEATURES

- 1 RU design fits 19-inch rack systems
- Four card slots or four independent video encoding or decoding systems
- Shallow rack depth requirement of 355mm
- Provides up to 150W of DC power to the function slots

OTHER

Compatible Blades

- BLE264-H4: 4 Ch HDMI H.264 Enc Blade
- BLE264-S4: 4 Ch SDI H.264 Enc Blade
- BLE264-FP: Blank face plates for unused slots
- BLD265-SC2: 2 Ch SDI or Composite H.265 Decoder Blade

SPECIFICATIONS

Power Input	90-264 VAC at 47-63 HZ, 125-370 VDC with IEC 60320-1 C14 compliant jack
Inrush current	Typ. 35A/115VAC, 70A/230VAC
Max Power Consumption	250W
Serial Port Jacks	16x 2.5mm barrel jacks for serial communication, 4 per slot
Temperature and Humidity	Operating: 0°C to 50°C 20-80% Relative Humidity non-condensing Storage: -10°C to 80°C 20-80% Relative Humidity non-condensing
Dimensions	436 x 355 x 44 mm (17.17 x 13.99 x 1.73 in)
Weight	9.8 lb (4.45 kg)

***Contact Z³ Technology for Customized Product Options**

sales@Z3technology.com

+1.402.323.0702

www.Z3technology.com