Z3Cam+HD^{TT} Z9520

EXPAND YOUR REACH H.265 HD IP Camera



- Real-Time HEVC/H.265 HD Video Streaming
- Full HD 30x Optical Zoom
- NDAA and TAA Compliant IP Camera
- Power over Ethernet (PoE)

Dotails

 \bullet Supports Sony VISCA $^{\rm m}$ camera control over IP and ONVIF Profile S & T

NEVER BEFORE HAS STREAMING BEEN SO SIMPLE AND COST-EFFECTIVE

The Z3Cam-HD[™] Z9520 H.265 IP camera provides HD video streaming over Gigabit Ethernet networks. Combining video compression expertise from Z3 Technology with Sony's proven CMOS sensor technology, the Z3Cam-HD provides the highest quality image at the lowest bandwidth, latency and power. A 7-pin Serial IO enables PTZ control and offers connection for GPS data overlay and a wide range of accessory items. This NDAA compliant Z3Cam-HD is the ideal IP Camera for surveillance, security, inspection, and other applications requiring TAA compliance. Sony's combined feature set of Wide Dynamic Range, ICR on Color for colorful low light performance, and super image stabilization is readily available with the Z3Cam-HD. **APPLICATIONS**

UAV

Inspection

Remote Monitoring

Security and Surveillance

Aerospace

Unmannec

Details	
Camera Features	 Full HD 30x optical zoom Super and Super+ Image Stabilization 2D/3D noise reduction algorithm for high frequency and high detail areas Wide Dynamic Range and Visibility enhancer auto ICR (Day and Night) High sensitivity image processor for low-light environments Spherical privacy zone masking and ROI support Leverages Sony's FCB-EV9520L HD camera block
Streaming Features	 H.265, H.264 or MJPEG encoded video over IP with no distance limitations Supports HD resolutions up to 60 fps (1080p, 720p, and lower) Outputs RTP, RTSP, MPEG-2 TS, RTMP*, RTMPS, or STR (Caller, Sender, Rendezvous, and SRT Encryption Simultaneously stream and/or record in multiple resolutions and bitrates Supports unicast and multicast streaming Compatible with Wowza Streaming Engine™, Facebook Live™, and YouTube Live*
Control	 Z3 web interface for control of camera and streaming features Pass Sony VISCA™Camera Controls over IP Supports ONVIF® Profile S & T Pelco-D PTZ control Easy-to-Use HTTPS-Based Control Interface with live-video previfew, API, or Serial/SSH
Recording	Compressed USB recording or NFS
Decoder Options	Compatible with ZEUS® SME-01 and DMD-4K decoders (also available from Z3 Technology) PC decoding / ONVIF

*In H.264 mode only

Specifications		Z3Cam·HD	
Interfaces	Gigabit Ethernet, USB 3.1, Audio Input, 7-pin Phoenix connector, RS-232 serial IO		
Supported Resolutions	1080p and 720p @ 60, 59.94, 50, 30, 29.97, 25fps		
Power	PoE or 12V DC		
Power Consumption	Less than 8W typical while encoding H.265/HEVC video		
Mount	1/4 20 UNC tripod screw hole on bottom of unit		
Temperature & Humidity	<i>Operating: -</i> 5 to 45°C at 20-80% Relative Non-Condensing Humidity	Storage:-10 to 60 °C at 20-80% Relative Non- Condensing Humidity	
Dimensions (L x W x H)	132 x 61 x 61 mm (5.2 x2.4 x2.4 in)		
Weight	698 g (1.5 lb)		
Package Contents	Z3Cam-HD camera, 12V Power Supply and Serial Cable		

HD IP STREAMING



Contact Z³ Technology for Customized Product Options sales@Z3technology.com +1.402.323.0702 www.Z3technology.com



Copyright 2023 Z³ Technology, LLC. Sony is a registered trademark of Sony Corporation. ZEUS is a registered trademark of Z3 Technology, LLC.

All content subject to change without notice. DOC-MKT-0197-03