

# Z3Cam-4K™ EXPAND YOUR REACH H.265 4K IP Camera

Model: 4K60



- Real-Time 4K Video Streaming at 60fps
- 30x zoom using Sony’s patented Stable Zoom
- Stream 4K and HD simultaneously
- Power over Ethernet (PoE)
- Supports Sony VISCA™ camera control over IP and ONVIF® Profile S & T

The Z3Cam-4K model 4K60 IP Camera offers full resolution streaming with Sony’s FCB-ER9500 block camera. With 25x Optical Zoom, Wide Dynamic Range, Image Stabilization and Superior Low Light Performance the Z3Cam-4K camera delivers immaculate focus at UHD Resolutions. Controls are seamlessly integrated into Z3 Technology’s easy-to-use Web User Interface. This flexible IP Camera allows you to send video and metadata in the stream, turn on video overlay capabilities and connect to a NTP server.

## APPLICATIONS

- Broadcast
- Industrial
- Medical
- Security and Surveillance
- Unmanned



## Details

Camera Features	<ul style="list-style-type: none"> <li>• 30x optical zoom in 2160p60 mode using Sony’s Stable Zoom</li> <li>• Noise reduction algorithm for high frequency and high detail areas</li> <li>• Wide Dynamic Range, 130 db</li> <li>• High sensitivity in Day and Night</li> <li>• Super Image Stabilizer</li> <li>• Flare Reduction with 7 Blade Iris</li> <li>• Vibrant Low Light Imaging with ICR on Color</li> <li>• Leverages Sony’s FCB-ER9500 4K camera module</li> </ul>
Streaming Features	<ul style="list-style-type: none"> <li>• H.265 or H.264 encoded video over IP with no additional equipment and no distance limitations</li> <li>• Supports 4K UHD and HD resolutions up to 60 fps (2160p, 1080p, 720p, and lower)</li> <li>• Outputs RTP, RTSP, MPEG-2 TS, RTMP, or SRT</li> <li>• Simultaneously stream and/or record in multiple resolutions and bitrates</li> <li>• Multi-line text overlay</li> <li>• Supports unicast and multicast streaming</li> <li>• Compatible with Wowza Streaming Engine™ and YouTube Live*</li> </ul>
Control	<ul style="list-style-type: none"> <li>• Z3 web interface for control and configuration</li> <li>• Pass Sony VISCA™ Camera Control over IP</li> <li>• Supports ONVIF® Profile S &amp; T</li> <li>• Pelco-D PTZ control</li> </ul>
Recording	<ul style="list-style-type: none"> <li>• Compressed USB or NFS recording</li> </ul>
Decoder Options	<ul style="list-style-type: none"> <li>• Compatible with ZEUS® DMD-4K decoder (also available from Z3 Technology)</li> <li>• PC decoding</li> </ul>



\*in H.264 mode only

## Specifications


Interfaces	Gigabit Ethernet, USB 3.1, Audio Input and Composite Output, RS-232, Serial I/O (RS-485, RS-422, and RS-232)	
Power	12V DC or PoE 802.af/at class 0	
Power Consumption	13W typical while encoding H.265/HEVC video	
Temperature & Humidity	Operating: -5 to 50 °C at 20-80% Relative Humidity	Storage:-10 to 60 °C at 20-80% Relative Humidity
Mount	1/4 20 UNC tripod screw hole on bottom of unit	
Dimensions (L x W x H)	164 x 61 x 62 mm (6.5 x 2.4 x 2.4 in)	
Weight	829 g (1.83 lb)	
Package Contents	Z3Cam-4K60 camera and 12V Power Supply	

## 4K IP STREAMING

**Z3CAM-4K60™**  
H.265/HEVC 4K  
Encoding & IP  
Streaming



Ethernet



HDMI



2160p60 H.265/HEVC PC Decoder

2160p60

**Z3CAM-4K60™**  
H.265/H.264 4K  
Encoding & IP  
Streaming



Ethernet




HDMI



**ZEUS® DMD-4K**  
2160p60 H.265 Decoder

2160p60

## OPERATING CONTROLS



- ① GbE w/ POE Support
- ② USB 3.1
- ③ RS-232 Serial
- ④ Status LED
- ⑤ RS-485/RS-422/RS-232\*
- ⑥ 12V DC Power
- ⑦ Audio Input

\*RS-485 Serial is for advanced users

## ORDERING OPTIONS

**Z3Cam-4K60™**  
*Complete Solution*

- 4K IP Camera
- Power Supply
- Serial Cable
- Documentation

Contact Z<sup>3</sup> Technology for Customized Product Options  
[sales@Z3technology.com](mailto:sales@Z3technology.com)    +1.402.323.0702    [www.Z3technology.com](http://www.Z3technology.com)

