





Z3
Technology®

Dual Camera Full 3G-SDI Encoder

Designed for your Visible & IR Encoding Needs

FSDI-15A

- H.265/H.264 Dual Camera Video Streaming
- Interfaces with SDI, LVDS, and Composite cameras
- Supports Visible and Thermal Cameras
- Low Latency Encoding With Simultaneous Streaming & Recording
- Camera Controls Sent over IP
- Pass KLV Metadata



The FSDI-15A is designed for dual camera inspection, surveillance, industrial and UAV applications. The flexibility of the system allows for a visible camera and an infrared camera. The system is capable of encoding and streaming H.265 and H.264 video. The encoder can be configured to stream over IP and simultaneously record to micro SD card, or NFS.

Technical

Interfaces

- 1x 3G-SDI Input
- 1x LVDS via KEL
- 1x Composite Input

• Visible Cameras	3G-SDI Cameras
• IR Cameras	LVDS*, NTSC/PAL/RS170*, Boson, Tau2, Tamarisk, Tenum
• Recording	USB, Micro SD, or NFS
• Additional Interfaces	PoE, Gigabit Ethernet, SDI Loop Out, Audio Input, RS-485, Composite Output, HDMI Output, UART, RS232 Serial
Video Codecs	H.265, H.264
Encoding Resolutions	1080p (up to 60fps), 720p, NTSC/PAL, VGA, CIF and QVGA
Output Formats	RTP, TSRTSP, RTSP, MPEG-2 TS, RTMPS, and RTMP

Features

- Low Latency, Low Power
- Ability to Resize HD Camera Input to Lower Resolutions Keeping Full Field of View
- Control via Easy-to-Use HTTP-Based Control Interface, API, or Serial/SSH
- Live video preview in the web GUI
- ONVIF® Profiles S & T Compliant
- Compatible with ZEUS® Video Decoders
- Pass Camera and PTZ Controls over IP
- Embedded KLV Metadata Support via SDI or Serial, MISB 0601 Compliant
- High Precision Timestamps Across Multiple Streams, MISB 0604 Compliant
- Multiline text Overlay via the Web Gui or the API
- Logo or Image overlay via the API
- NMEA GPS Overlay
- Region of Interest: Configurable Field of View
- AI Ready for on the edge analytics

Specifications

Encoder Board Size	58 x 58 x 46 mm (2.28 x 2.28 x 1.81 in)
Encoder Board Weight	50g (heat pipe is an additional 25g)
Power Consumption	4.5W typical while encoding 2 cameras in H.265 Video



ORDERING OPTIONS

FSDI-15A-RPS OEM Starter Kit

- FSDI-13A Encoder Boards
- Power Supply
- Software SDK
- Documentation
- Serial Cable
- MMCX to BNC Cable
- KEL Ribbon Cable

Note: Camera sold separately

FSDI-15A OEM Production Set

- FSDI-13A Encoder Boards

Note: Camera and cables sold separately

APPLICATIONS

Unmanned Systems


Military Systems

Inspection


Surveillance

HW Block Diagram

FSDI-15A Encoder (H.265 1080p60 + Composite)



Use Case



***Contact Z³ Technology for Customized Product Options**
sales@Z3technology.com +1.402.323.0702 www.Z3technology.com



Z³ Technology[®]

Z³ Technology is an industry-leading, USA-based manufacturer of production-ready embedded multimedia solutions and IP camera systems. From our founders to our world-class engineers to our sales and customer service team, we understand your requirements and speak your language. Our experience allows us to provide cost-effective solutions to meet your multimedia product requirements. With the assistance of our robust worldwide distribution and sales networks, we can provide a simple solution for your multimedia needs.